

# Field Stop Trench IGBT

## 40 A, 650 V

### AFGHL40T65SPD

#### Description

Using the novel field stop 3<sup>rd</sup> generation IGBT technology, AFGHL40T65SPD offers the optimum performance with both low conduction loss and switching loss for a high efficiency operation in various applications, which provides 50 V higher blocking voltage and rugged high current switching reliability.

Meanwhile, this part also offers an advantage of outstanding performance in parallel operation.



#### Features

- AEC-Q101 Qualified
- Low Saturation Voltage:  $V_{CE(Sat)} = 1.85 \text{ V (Typ.) @ } I_C = 40 \text{ A}$
- 100% Of The Part Are Dynamically Tested (Note 1)
- Short Circuit Ruggedness  $> 5 \mu\text{S @ } 25^\circ\text{C}$
- Maximum Junction Temperature:  $T_J = 175^\circ\text{C}$
- Fast Switching
- Tight Parameter Distribution
- Positive Temperature Co-efficient for Easy Parallel Operating
- Co-Packed With Soft And Fast Recovery Diode


#### Typical Applications

- On-board Charger
- Air Conditioner Compressor
- PTC Heater
- Motor Drivers
- Other Automotive Power-Train Applications

| $V_{CES}$ | $E_{on}$ | $V_{CE(Sat)}$ |
|-----------|----------|---------------|
| 650 V     | 1.16 mJ  | 1.85 V        |



#### MARKING DIAGRAM



|               |                                 |
|---------------|---------------------------------|
| \$Y           | = onsemi Logo                   |
| &Z            | = Assembly Plant Code           |
| &3            | = 3-Digit Data code             |
| &K            | = 2-Digit Lot Traceability code |
| AFGHL40T65SPD | = Specific Device Code          |

#### ORDERING INFORMATION

| Device        | Package   | Shipping        |
|---------------|-----------|-----------------|
| AFGHL40T65SPD | TO-247-3L | 30 Units / Rail |

# AFGHL40T65SPD

## ABSOLUTE MAXIMUM RATINGS ( $T_C = 25^\circ\text{C}$ , Unless otherwise noted)

| Symbol    | Description  | Ratings     | Units            |
|-----------|--|-------------|------------------|
| $V_{CES}$ | Collector to Emitter Voltage   | 650         | V                |
| $V_{GES}$ | Gate to Emitter Voltage  | $\pm 20$    | V                |
|           | Transient Gate to Emitter Voltage  | $\pm 30$    | V                |
| $I_C$     | Collector Current @ $T_C = 25^\circ\text{C}$                                       | 80          | A                |
|           | Collector Current @ $T_C = 100^\circ\text{C}$                                      | 40          |                  |
| $I_{CM}$  | Pulsed Collector Current (Note 2)  | 120         | A                |
| $I_F$     | Diode Forward Current @ $T_C = 25^\circ\text{C}$                                   | 40          | A                |
|           | Diode Forward Current @ $T_C = 100^\circ\text{C}$                                  | 20          |                  |
| $I_{FM}$  | Pulsed Diode Maximum Forward Current (Note 2)                                      | 120         | A                |
| $P_D$     | Maximum Power Dissipation @ $T_C = 25^\circ\text{C}$                               | 267         | W                |
|           | Maximum Power Dissipation @ $T_C = 100^\circ\text{C}$                              | 134         |                  |
| SCWT      | Short Circuit Withstand Time @ $T_C = 25^\circ\text{C}$                            | 5           | $\mu\text{s}$    |
| $T_J$     | Operating Junction Temperature   | -55 to +175 | $^\circ\text{C}$ |
| $T_{stg}$ | Storage Temperature Range  | -55 to +175 | $^\circ\text{C}$ |
| $T_L$     | Maximum Lead Temp. For soldering Purposes, $\frac{1}{8}$ " from case for 5 seconds | 300         | $^\circ\text{C}$ |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

- $V_{CC} = 400\text{ V}$ ,  $V_{GE} = 15\text{ V}$ ,  $I_C = 120\text{ A}$ ,  $R_G = 20\ \Omega$ , Inductive Load.
- Repetitive rating: pulse width limited by max. Junction temperature.

## THERMAL CHARACTERISTICS

| Symbol          | Rating   | Max. | Units                     |
|-----------------|--|------|---------------------------|
| $R_{\theta JC}$ | Thermal Resistance Junction to Case, for IGBT  | 0.43 | $^\circ\text{C}/\text{W}$ |
| $R_{\theta JC}$ | Thermal Resistance Junction to Case, for Diode | 1.69 | $^\circ\text{C}/\text{W}$ |
| $R_{\theta JA}$ | Thermal Resistance Junction to Ambient         | 40   | $^\circ\text{C}/\text{W}$ |

# AFGHL40T65SPD

## ELECTRICAL CHARACTERISTICS (T<sub>C</sub> = 25°C unless otherwise noted)

| Parameter   | Test Conditions  | Symbol            | Min. | Typ. | Max. | Unit |
|---|--|-------------------|------|------|------|------|
| <b>OFF CHARACTERISTICS</b>  |  |                   |      |      |      |      |
| Collector-emitter Breakdown Voltage, Gate-emitter Short-circuited | V <sub>GE</sub> = 0 V, I <sub>C</sub> = 1mA  | BV <sub>CES</sub> | 650  | -    | -    | V    |
| Temperature Coefficient of Breakdown Voltage                      | V <sub>GE</sub> = 0 V, I <sub>C</sub> = 1mA  |                   | -    | 0.6  | -    | V/°C |
| Collector-emitter Cut-off Current, Gate-emitter Short-circuited   | V <sub>GE</sub> = 0 V, V <sub>CE</sub> = 650 V<br>V <sub>GE</sub> = 0 V, V <sub>CE</sub> = 650 V, T <sub>J</sub> = 175°C | IC <sub>ES</sub>  | -    | -    | 250  | μA   |
| Gate Leakage Current, Collector-emitter Short-circuited           | V <sub>GE</sub> = 20 V, V <sub>CE</sub> = 0 V  | IG <sub>ES</sub>  | -    | -    | ±400 | nA   |

## ON CHARACTERISTICS

|                                      |  |                      |     |              |     |   |
|--------------------------------------|--|----------------------|-----|--------------|-----|---|
| Gate-emitter Threshold Voltage       | V <sub>GE</sub> = V <sub>CE</sub> , I <sub>C</sub> = 40 mA   | V <sub>GE(th)</sub>  | 4.0 | 5.0          | 7.5 | V |
| Collector-emitter Saturation Voltage | V <sub>GE</sub> = 15 V, I <sub>C</sub> = 40 A<br>V <sub>GE</sub> = 15 V, I <sub>C</sub> = 40 A, T <sub>J</sub> = 175°C | V <sub>CE(sat)</sub> | 1.4 | 1.85<br>2.51 | 2.4 | V |

## DYNAMIC CHARACTERISTICS

|                              |  |                  |   |      |   |    |
|------------------------------|--|------------------|---|------|---|----|
| Input Capacitance            | V <sub>CE</sub> = 30 V, V <sub>GE</sub> = 0 V, f = 1 MHz               | C <sub>ies</sub> | - | 1518 | - | pF |
| Output Capacitance           |  | C <sub>oes</sub> | - | 91   | - |    |
| Reverse Transfer Capacitance |  | C <sub>res</sub> | - | 15   | - |    |
| Gate Charge Total            | V <sub>CE</sub> = 400 V, I <sub>C</sub> = 40 V, V <sub>GE</sub> = 15 V | Q <sub>g</sub>   | - | 36   | - | nC |
| Gate to Emitter Charge       |  | Q <sub>ge</sub>  | - | 11   | - |    |
| Gate to Collector Charge     |  | Q <sub>gc</sub>  | - | 12   | - |    |

## SWITCHING CHARACTERISTICS

|                         |  |                  |   |      |   |    |
|-------------------------|--|------------------|---|------|---|----|
| Turn-on Delay Time      | T <sub>C</sub> = 25°C<br>V <sub>CC</sub> = 400 V, I <sub>C</sub> = 40 A<br>R <sub>g</sub> = 6 Ω<br>V <sub>GE</sub> = 15 V<br>Inductive Load, T <sub>C</sub> = 25°C | td(on)           | - | 18   | - | ns |
| Rise Time               |  | t <sub>r</sub>   | - | 42   | - |    |
| Turn-off Delay Time     |  | td(off)          | - | 35   | - |    |
| Fall Time               |  | t <sub>f</sub>   | - | 10   | - | mJ |
| Turn-on Switching Loss  |  | E <sub>on</sub>  | - | 1.16 | - |    |
| Turn-off Switching Loss |  | E <sub>off</sub> | - | 0.27 | - |    |
| Total Switching Loss    |  | E <sub>ts</sub>  | - | 1.43 | - |    |
| Turn-on Delay Time      | T <sub>C</sub> = 175°C<br>V <sub>CC</sub> = 400 V, I <sub>C</sub> = 40 A<br>R <sub>g</sub> = 6 Ω<br>V <sub>GE</sub> = 15 V<br>Inductive Load                       | td(on)           | - | 16   | - | ns |
| Rise Time               |  | t <sub>r</sub>   | - | 40   | - |    |
| Turn-off Delay Time     |  | td(off)          | - | 37   | - |    |
| Fall Time               |  | t <sub>f</sub>   | - | 11   | - | mJ |
| Turn-on Switching Loss  |  | E <sub>on</sub>  | - | 1.59 | - |    |
| Turn-off Switching Loss |  | E <sub>off</sub> | - | 0.42 | - |    |
| Total Switching Loss    |  | E <sub>ts</sub>  | - | 2.01 | - |    |

## DIODE CHARACTERISTICS

|                         |   |                  |     |            |     |    |
|-------------------------|---|------------------|-----|------------|-----|----|
| Forward Voltage         | I <sub>F</sub> = 20 A<br>I <sub>F</sub> = 20 A, T <sub>J</sub> = 175°C          | V <sub>F</sub>   | 1.4 | 2.2<br>1.9 | 2.7 | V  |
| Reverse Recovery Time   | T <sub>J</sub> = 25°C<br>I <sub>F</sub> = 20 A, di <sub>F</sub> /dt = 200 A/μs  | t <sub>rr</sub>  | -   | 35         | -   | ns |
| Reverse Recovery Charge |   | Q <sub>rr</sub>  | -   | 58         | -   | μC |
| Reverse Recovery Time   | T <sub>J</sub> = 175°C<br>I <sub>F</sub> = 20 A, di <sub>F</sub> /dt = 200 A/μs | t <sub>rr</sub>  | -   | 214        | -   | ns |
| Reverse Recovery Charge |   | Q <sub>rr</sub>  | -   | 776        | -   | μC |
| Reverse Recovery Energy |   | E <sub>rec</sub> | -   | 51         | -   | μJ |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

TYPICAL PERFORMANCE CHARACTERISTICS




Figure 1. Typical Output Characteristics




Figure 2. Typical Output Characteristics




Figure 3. Typical Saturation Voltage Characteristics




Figure 4. Transfer Characteristics




Figure 5. Saturation Voltage vs. Case Temperature at Variant Current Level




Figure 6. Saturation Voltage vs.  $V_{GE}$

TYPICAL PERFORMANCE CHARACTERISTICS (Continued)




Figure 7. Saturation Voltage vs.  $V_{GE}$




Figure 8. Saturation Voltage vs.  $V_{GE}$




Figure 9. Capacitance Characteristics




Figure 10. Gate charge Characteristics




Figure 11. SOA Characteristics




Figure 12. Turn off Switching SOA Characteristics

TYPICAL PERFORMANCE CHARACTERISTICS (Continued)




Figure 13. Turn-on Characteristics vs. Gate Resistance




Figure 14. Turn-off Characteristics vs. Gate Resistance




Figure 15. Turn-on Characteristics vs. Collector Current




Figure 16. Turn-off Characteristics vs. Collector Current




Figure 17. Switching Loss vs Gate Resistance




Figure 18. Switching Loss vs Collector Current

TYPICAL PERFORMANCE CHARACTERISTICS (Continued)




Figure 19. Forward Characteristics




Figure 20. Reverse Current




Figure 21. Stored Charge




Figure 22. Reverse Recovery Time




Figure 23. Reverse Recovery Current

# AFGHL40T65SPD

## TYPICAL PERFORMANCE CHARACTERISTICS (Continued)




Figure 24. Transient Thermal Impedance of IGBT






Figure 25. Transient Thermal Impedance of Diode

**TO-247-3LD**  
**CASE 340CX**  
**ISSUE A**

DATE 06 JUL 2020



NOTES: UNLESS OTHERWISE SPECIFIED.

- A. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH, AND TIE BAR EXTRUSIONS.
- B. ALL DIMENSIONS ARE IN MILLIMETERS.
- C. DRAWING CONFORMS TO ASME Y14.5 - 2009.
- D. DIMENSION A1 TO BE MEASURED IN THE REGION DEFINED BY L1.
- E. LEAD FINISH IS UNCONTROLLED IN THE REGION DEFINED BY L1.

**GENERIC MARKING DIAGRAM\***



- XXXXX = Specific Device Code
- A = Assembly Location
- Y = Year
- WW = Work Week
- G = Pb-Free Package

\*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.

| DIM | MILLIMETERS |       |       |
|-----|-------------|-------|-------|
|     | MIN         | NOM   | MAX   |
| A   | 4.58        | 4.70  | 4.82  |
| A1  | 2.20        | 2.40  | 2.60  |
| A2  | 1.40        | 1.50  | 1.60  |
| D   | 20.32       | 20.57 | 20.82 |
| E   | 15.37       | 15.62 | 15.87 |
| E2  | 4.96        | 5.08  | 5.20  |
| e   | ~           | 5.56  | ~     |
| L   | 19.75       | 20.00 | 20.25 |
| L1  | 3.69        | 3.81  | 3.93  |
| ØP  | 3.51        | 3.58  | 3.65  |
| Q   | 5.34        | 5.46  | 5.58  |
| S   | 5.34        | 5.46  | 5.58  |
| b   | 1.17        | 1.26  | 1.35  |
| b2  | 1.53        | 1.65  | 1.77  |
| b4  | 2.42        | 2.54  | 2.66  |
| c   | 0.51        | 0.61  | 0.71  |
| D1  | 13.08       | ~     | ~     |
| D2  | 0.51        | 0.93  | 1.35  |
| E1  | 12.81       | ~     | ~     |
| ØP1 | 6.60        | 6.80  | 7.00  |

|                         |                    |  |
|-------------------------|--------------------|--|
| <b>DOCUMENT NUMBER:</b> | <b>98AON93302G</b> | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| <b>DESCRIPTION:</b>     | <b>TO-247-3LD</b>  | <b>PAGE 1 OF 1</b>   |

onsemi and Onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.

**onsemi**, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## ADDITIONAL INFORMATION

### TECHNICAL PUBLICATIONS:

Technical Library: [www.onsemi.com/design/resources/technical-documentation](http://www.onsemi.com/design/resources/technical-documentation)  
onsemi Website: [www.onsemi.com](http://www.onsemi.com)

### ONLINE SUPPORT: [www.onsemi.com/support](http://www.onsemi.com/support)

For additional information, please contact your local Sales Representative at [www.onsemi.com/support/sales](http://www.onsemi.com/support/sales)

